SPORTS | LEISURE

Regupol®

Golf Clubs

Rubber Flooring for indoors and outdoors

spike resistant · durable · resilient



www.berleburger.de

SPORTS | LEISURE

Rubber Flooring for indoors and outdoors



Spike resistant · durable · resilient

Each individual game requires its own sports facility, equipment and accessories intensive. Golf is no exception to that and in golf club facilities a special flooring material is required that can withstand intensive daily foot traffic as well as mechanical stress through spikes and caddies. The spike shoes are particularly tough on the surface and will destroy most conventional type flooring materials. The spikes themselves can wear off as quickly if those are used on a blank concrete surface. Therefore, the flooring material in a golf club must be cushioning, hard wearing, slip resistant and spike resistant under indoor and outdoor conditions. BSW has developed many products with exactly these characteristics. These products have proven their quality and their excellent performance rating over many years in golf club facilities throughout the world.

The benefits

- spike resistant and resistant against other mechanical stress
- slip resistant
- long-lasting
- abrasion resistant

- comfortable to walk on due to cushioning effect
- environmentally safe
- sound absorbing
- easy to install and maintain

For indoor applications a wide range of custom colour combinations can be offered for individual designs.



Installatio

Interlocking pa imi ar to insta

lt si

01 re crushed ne bas the join veen t tively: P e fully concrete special po

The

r<mark>locking p</mark> ng rang Inte D

Everline Stoneline

caddy rooms, Indoor oyers and pro shop roop

Regupol Elastic tiles: Driving ranges and walking paths

Everline Individual and Stoneline Individual:

Please refer to Everline and Stoneline. pecially suitable for all areas in the club e a very special style is focused on in f colours and colour combinations.



structurally sound, dry and cice



Surface for outdoors

Regupol interlocking pavers *



Regupol Interlocking pavers are perfectly suitable for all outdoor areas and paths where people are walking and driving on, especially for driving ranges and walkways. The compact pavers are easy to interconnect and can be combined with concrete pavers due to their shape and measurements. They are extremely resilient and durable even under tough conditions, including spike penetration and vehicle traffic. Beginners and half pieces are available for the perimeter of an installation. Colours: redbrown, green, black

Dimension	Weight
200 x 160 x 43 mm	approx. 39 kg/m ²
200 x 160 x 21 mm*	* approx. 20 kg/m ²

** 21 mm split pavers must be fully bonded to an engineered subbase.

There are certain tolerances as far as the dimensional stability and accuracy of the Interlocking pavers are concerned. The tolerance is +/-3 mm in thickness and +/-5 mm in length and width.





Regupol Elastic tiles *



Regupol Elastic tiles are equally resistant against spike traffic, similar to the whole portfolio of flooring products for golf available from BSW. The tiles are easy to install and extremely durable. They are best suitable for walkways, yet they are a good fit for other areas, too.

Colours: redbrown, green, black

Dimension

1.000 x 500 x 15 mm	approx. 12 kg/m ²
1.000 x 500 x 22 mm	approx. 18 kg/m ²
1.000 x 500 x 30 mm	approx. 24 kg/m ²
1.000 x 500 x 43 mm	approx. 35 kg/m ²
1.000 × 300 × 43 mm	appion. 55 kg/iii

Weight

"Shadow centre joint at 500 mm for square appearance".

Regupol EPDM Elastic tiles *



This version of Regupol elastic tiles is supplied with a special EPDM top layer. The EPDM rubber granules used for the top layer are extremely colour consistent, under all kinds of weather conditions. The durability and colour stability of these tiles is excellent. The EPDM elastic tiles are as resilient and shock absorbing as the standard elastic tiles which makes them perfectly suitable in many areas of a golf club facility. **Colours:** redbrown/black, green/black, beige/black, non-standard colours available upon request

Dimension

1.000 x 500 x 30 mm 1.000 x 500 x 40 mm Weight

approx. 22 kg/m² approx. 29 kg/m²

"Shadow centre joint at 500 mm for square appearance".



EVERROLL – YOUR SELECTION



Everroll Classic



black / red



black / green



black / blue



black / grey

Six colour groups in five designs each are reflecting our new Everroll collection. The five designs Uni, Stone, Endurance, Vision and Star are non-directional. The six colour groups (vertically) Goa, Kush, Berlin, Nome, London and Nassau are repeatedly intercharged and can be combined perfectly. Altogether, 30 designs, which can be combined harmonically, are possible to be put together.

Nassau

Nome









pigeon blue / light grey / eggshell / black

Everroll is suitable in caddy rooms, changing rooms, foyers and shops. Everroll is the perfect floor covering for those areas where the floor is expected to withstand heavy traffic and mechanical stress such as the spike traffic trough golf shoes. Everroll is spike resistant at a minimum thickness of 10 mm. It reduces impact sound, it is easy on joints and ligaments and offers a high level of shock absorption.



London











capri blue / pigeon blue / black



signal green / capri blue / black

Technical data

Roll width Length Standard	1,250 10-40 metres
thicknesses	Vision, Star 4 and 8 mm Uni, Stone, Endurance 4 mm Everroll Classic 4, 6, 8, 10, 12 mm other thicknesses on demand
Material	
composition	Rubber and EPDM granules, PUR binder
Installation	Permanently adhered or taped, subject to site conditions

uni, dominating colour of colour group ____

identical colour contents, fine granulate

50 percent black, 50 percent other colours, medium granulate

80 percent black, 20 percent other colours, medium granulate

colours, large granulate

_

80 percent black, 20 percent other







What else is in the BSW range: Regupol surface coverings for people who keep horses

Whether in the stable, paddock or exercise area, on washing areas or walking paths, in horse clinics or breeding stations, Regupol floor and wall coverings set a benchmark in terms of animal health, hygiene, resilience and saving money. The wide range of different installation components makes a significant contribution to the health of the animals and reduces considerably the amount of bedding that has to be used and the amount of work required in terms of cleaning and maintenance. Regupol[®] is the material which Berleburger Schaumstoffwerk GmbH (BSW) uses to create a wide range of floor coverings for sport, fitness, health and leisure. Regupol[®] is a mixture of rubber and polyurethane. The rubber is processed at BSW's production facilities using

BSW (Berleburger Schaumstoffwerk) has been manufacturing Pagunol® products for the sports

manufacturing Regupol® products for the sports industry for over 30 years: floor coverings, sports mats, athletic tracks, multipurpose courts, elastic pads and safety surfacing. BSW is still able to offer more. The product portfolio supplied to the construction industry is just as comprehensive as the range for sports facilities. And BSW is one of the leaders in this market segment, too. Regupol® is a registered trade-mark of BSW. Regupol® is currently manufactured and marketed by BSW GmbH in Germany and by Regupol Australia Pty. resistant and fully recyclable. Individual production runs for particular projects, customeroriented manufacture and storage ensure quick and user-specific solutions in every situation.

various formulas to meet special requirements.

Regupol[®] products are long lasting, stress

www.berleburger.de

You can find more information about our sports surfaces and other products on our website. You can also order product samples on-line, see a list of references and contact your local BSW adviser directly.

> Colour variances are possible between different production lots of the particular flour coverings.



Certified according to DIN EN ISO 9001 DIN EN ISO 14001 OHSAS 18001

/// BSW

Berleburger Schaumstoffwerk GmbH Postfach 1180 57301 Bad Berleburg (Germany) Telephone +49 2751 803-0 Telefax +49 2751 803-109 E-Mail info@berleburger.de Internet www.berleburger.de



Manufactured in accordance with highest industrial safety and environmental standards. Award winning manufacturing process. 3SW G GB 01 02 07